

IN THE CLAIMS:

1. (currently amended) A basket for a washing machine, said basket comprising:

a body comprising an outer peripheral wall and at least one rib extending radially inward from said outer peripheral wall, said rib comprising at least a first portion having a first cross section and a second portion having a second cross section, said second cross section different from said first cross section, said outer peripheral wall including a plurality of apertures therethrough, said apertures arranged in single vertically aligned columns between adjacent ribs;

wherein said rib comprises a face and substantially planar opposing sides extending from said face, said basket further comprising ~~at least one support~~ a plurality of supports, each of said plurality of supports extending radially outward from said face toward said outer peripheral wall, and extending between said opposing sides of said rib such that each said ~~at least one support~~ support is substantially flush with said outer peripheral wall, said plurality of supports spaced apart in a direction substantially parallel to a rotational axis of said basket such that portions of said rib are hollow between adjacent supports and solid at said supports from said face and said opposing sides to said outer peripheral wall.

2. (original) A basket in accordance with Claim 1 wherein said rib extends substantially vertically.

3. (canceled)

4. (original) A basket in accordance with Claim 1 wherein said first portion is substantially rectangular in cross section.

5. (original) A basket in accordance with Claim 1 wherein said rib extends radially inward from said outer wall for a distance of about 0.395 to about 1.5 inches.

6. (currently amended) A washing machine basket comprising:

an outer peripheral wall having an outer surface;

a plurality of ribs projecting radially inwardly from said outer peripheral wall, each said rib comprising a face and substantially planar opposing sides extending from said face,

and a first end and a second end, said first end projecting a first radial distance from said outer peripheral wall, said second end projecting a second radial distance from said outer peripheral wall, said first radial distance less than said second radial distance;

a plurality of apertures formed in said outer peripheral wall, said apertures arranged in single vertically aligned columns between adjacent ribs; and

~~at least one support~~ a plurality of supports each extending radially outwardly from said face toward said outer peripheral wall, and extending between said opposing sides to a position of said rib such that each said support is substantially flush with said outer surface, said plurality of supports spaced apart in a direction substantially parallel to a rotational axis of said basket such that portions of said rib are hollow between adjacent supports and solid at said supports from said face and said opposing sides to said outer peripheral wall.

7. (original) A basket in accordance with Claim 6, said rib comprising a transition portion projecting a variable distance from said outer wall, said variable distance ranging from said first radial distance to said second radial distance.

8. (original) A basket in accordance with Claim 7 wherein said variable distance is about 0.395 inches to about 1.5 inches.

9. (original) A basket in accordance with Claim 7, said transition portion further having a varying width.

10. (currently amended) A washing machine basket comprising:

an outer peripheral wall and a plurality of vertically extending ribs projecting radially inwardly from said outer peripheral wall at a distance of about 0.395 to about 1.5 inches, said outer peripheral wall including a plurality of apertures therethrough, said apertures arranged in single vertically aligned columns between adjacent ribs; and

wherein each said rib comprises a face and substantially planar opposing sides extending from said face, said basket further comprising ~~at least one support~~ a plurality of supports, each of said plurality of supports extending radially outward from said face toward said outer peripheral wall, and extending between said opposing sides of said rib such that each said at least one support support is substantially flush with said outer peripheral wall, said plurality of supports spaced apart in a direction substantially parallel to a rotational axis

of said basket such that portions of said rib are hollow between adjacent supports and solid at said supports from said face and said opposing sides to said outer peripheral wall.

11. (previously presented) A basket in accordance with Claim 10, wherein said apertures are outwardly flared.

12. (original) A basket in accordance with Claim 10 wherein said ribs are outwardly flared at one end thereof.

13. (canceled)

14. (currently amended) A basket in accordance with Claim 10 further comprising at least one circumferential support band extending from ~~said at least one supported of said plurality of supports~~, said at least one circumferential support band extending around an outer surface of said outer wall.

15. (original) A basket in accordance with Claim 10 wherein a portion of said rib is substantially triangular.

16. (currently amended) A washing machine basket comprising:

a substantially cylindrical outer peripheral wall and a plurality of inwardly projecting ribs depending therefrom, each said rib comprising:

a first portion having a first radially extending height from said outer peripheral wall and a first tangential width; and

a second portion having a second radially extending height from said outer peripheral wall and a second tangential width, said first height less than said second height, said first width greater than said second width;

wherein, said outer peripheral wall includes a plurality of apertures therethrough, said apertures arranged in single vertically aligned columns between adjacent ribs; and

wherein said rib comprises a face and substantially planar opposing sides extending from said face, said basket further comprising ~~at least one support~~ a plurality of supports, each of said plurality of supports extending radially outward from said face toward said outer peripheral wall, and extending between said opposing sides of said rib such that each said at

~~least one support~~ support is substantially flush with said outer peripheral wall, said plurality of supports spaced apart in a direction substantially parallel to a rotational axis of said basket such that portions of said rib are hollow between adjacent supports and solid at said supports from said face and said opposing sides to said outer peripheral wall.

17. (original) A basket in accordance with Claim 16 wherein said first height and said second height are in a range from about 0.395 to about 1.5 inches.

18. (original) A basket in accordance with Claim 16 wherein said first portion is substantially rectangular and said second portion is substantially triangular.

19. (currently amended) A washing machine comprising:

a cabinet; and

a basket rotatably mounted in said cabinet, said basket comprising an outer peripheral wall and a plurality of radially inwardly projecting ribs extending from said outer peripheral wall, said ribs having a varying width between ends thereof, said basket further including a plurality of apertures therethrough, said apertures arranged in single vertically aligned columns between adjacent ribs; and

wherein each said rib comprises a face and substantially planar opposing sides extending from said face, said basket further comprising ~~at least one support~~ a plurality of supports, each of said plurality of supports extending radially outward from said face toward said outer peripheral wall, and extending between said opposing sides of said rib such that each said at least one support is substantially flush with said outer peripheral wall, said plurality of supports spaced apart in a direction substantially parallel to a rotational axis of said basket such that portions of said rib are hollow between adjacent supports and solid at said supports from said face and said opposing sides to said outer peripheral wall.

20. (original) A washing machine in accordance with Claim 19, said ribs extending inwardly from said outer wall at a height of approximately 0.395 to 1.5 inches.